

GENERAL

Warm-up time:	30 seconds
First output speed:	Full colour: 14 seconds
	B/W: 14 seconds
Print speed:	Full colour: 20 pages per minute
	B/W: 20 pages per minute
CPU:	Intel Celeron-M: 350/400 MHz
Memory:	Standard: 128/256 MB
Duty cycle:	30,000 prints per month
Duplex:	Yes
Dimensions (W x D x H):	400/420 x 450/493 x 320/460 mm
Weight:	23.8/29 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER (SP C250SF)

Copying process:	Laser beam scanning and electro- photographic printing
Multiple copying:	Up to 99 copies
Resolution:	600 x 600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6, PostScript® 3™ , PictBridge
Print resolution:	Maximum: 2400 x 600 dpi
Fonts:	PCL (80 fonts)
Interface:	Standard: USB 2.0, Ethernet 10 base- T/100 base-TX, Wireless LAN (IEEE 802.11b/g/n)
Network protocol:	TCP/IP, Bonjour, IPP
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012
Mac OS environments:	Macintosh OS X Native v10.6 or later

SCANNER (SP C250SF)

Resolution:	Standard: 1,200 - 1,200 dpi
Scanning area:	Main scan: 216 mm
Scan mode:	B/W
	Greyscale
	Full colour
File format:	Single page TIFF, Single page JPEG,
	Single page PDF, Single page High
	compression PDF, Multi page TIFF,
	Multi page PDF
Bundled drivers:	Network TWAIN
Scan to:	E-mail, Folder

FAX (SP C250SF)

Circuit:	PSTN, PBX	
Compatibility:	G3	
Resolution:	8 x 3.85 line/mm, 200 x 100 dpi	
Compression method:	MH, MR, MMR, JBIG	
Modem speed:	Maximum: 33.6 Kbps	
Memory backup:	Yes	



www.ricoh-europe.com

PAPER HANDLING

Recommended paper size:	A4, A5, A6, B5, B6
Paper input capacity:	Standard: 251 sheets
	Maximum: 751 sheets
Paper output capacity:	Maximum: 150 sheets
Paper weight:	Standard paper tray(s): 60 - 160 g/m ² Optional paper tray(s): 60 - 105 g/m ² Bypass tray: 60 - 160 g/m ² Duplex: 60 - 90 g/m ²
Media capability:	Plain paper, Middle thick paper, Thick paper, Recycled paper, Colour paper, Letterhead, Pre-printed paper, Thin paper, Label paper, Envelopes, Bond, Cardstock

ECOLOGY

Power consumption:

Maximum: 1,300 W Energy Saver mode: 3.8 W

OPTIONS

1 x 500-sheet paper tray

CONSUMABLES

All-in-one cartridge capacity:	Black: 2,000 prints Cyan: 1,600 prints Magenta: 1,600 prints Yellow: 1,600 prints
Starter kit:	Black: 1,000 prints Cyan: 1,000 prints Magenta: 1,000 prints Yellow: 1,000 prints

Consumable yield measuring method ISO/IEC 19798. SP C2520SF: Copy speed Germany: 14 cpm; Belgium, Austria: 9 cpm.

For availability of models, options and software, please consult your local Ricoh supplier.

> ISO9001 certified, ISO14001 certified, ISO27001 certified All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2014 Ricoh Europe PLC. All rights

reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.